




4.8GHz-5.0GHz, 55W, 50V GaN fully matched PA Module

Description

The SMAV4850-55 is a 55-watt, integrated 2-stage Power Amplifier Module, designed for 5G massive MIMO applications, with frequencies from 4.8 to 5.0 GHz. The module is 50 Ω input and output fully matched, and requires minimal external components. The module offers a much smaller footprint than traditional discrete component solutions, with much less sensitivity for production, housed in 10*6mm cost effective plastic open cavity package.

The module incorporates a Doherty circuit delivering high power added efficiency for the entire module at 8W average power.



- Innegration owns the patents for internal Doherty architecture, and related plastic open cavity.

● Typical Performance of Doherty Demo (On Innegration fixture with device soldered):

VDS= 48V, IDQ=55mA, Vpeak=-4.9V				
Pout=39.5dBm				
Freq (MHz)	Ppeak(dBm)	Gain (dB)	EFF (%)	ACPR (dBc)
4800	48.49	28.7	40.5	-28.6
4900	48.49	28.8	41.0	-29.7
5000	48.38	28.3	40.2	-30.9


Notes:

- (1) WCDMA signal: 3GPP test model 1; 1 to 64 DPCH; Channel Bandwidth=3.84MHz, PAR =10.5 dB at 0.01 % probability on CCDF.

Features

- Industry leading RF performance for N79 5G MIMO AAU, for instance
 - ✓ 64T:320 W / 160MHz
- Plastic open cavity without molding compound brings advantage compared to molded design
 - ✓ Minimize the risk of high density thermal distribution in fanless system for longer life time
 - ✓ Highly consistent RF performance for yield of volume production
- 50 Ω Input/output matched,
- Integrated Doherty Final and driver Stage
- 6x10 mm Surface Mount Package, full copper flange underneath for grounding and heat dissipation

Pin Configuration and Description





Pin No.	Symbol	Description
1	VD1	Driver Amplifier, Drain Bias
4	VG1	Driver Amplifier, Gate Bias
6	RF IN	RF Input
11	VG3	Carrier Amplifier, Gate Bias
16	BE	VBW Enhance
19	RF OUT	RF Output
27	VD2	Peaking Amplifier, Drain Bias
32	VG2	Peaking Amplifier, Gate Bias
3,8-10,14-15,17,21,22,24,26,28,29,33-35	NC	No connection
2,5,7,12,13,18,20,23,25,30,31,36	GND	Internal Grounding, recommend connecting to Epad ground
Package Base	GND	DC/RF Ground. Must be soldered to EVB ground plane over array of vias for thermal and RF performance. Solder voids under Pkg Base will result in excessive junction temperatures causing permanent damage.

Table 1. Maximum Ratings

Rating	Symbol	Value	Unit
Drain--Source Voltage	V_{DSS}	200	Vdc
Gate--Source Voltage	V_{GS}	-8 to +0.6	Vdc
Operating Voltage	V_{DD}	+55	Vdc
Storage Temperature Range	T_{stg}	-65 to +150	°C
Case Operating Temperature	T_c	+150	°C
Operating Junction Temperature	T_j	+225	°C

Table 2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance@Average Power, Junction to Case $T_{case}=+85^{\circ}C$, CW Test, $P_{out}=9W$,	$R_{\theta JC}$	4.2	°C/W

Notes:

- (1) The thermal resistance is acquired by our company's FEA model, which was calibrated by IR measurement, the value shall be applied to reliability.
- (2) The reference T_{case} temperature $85^{\circ}C$ is apply on the backside of package.
- (3) If the device soldering onto the 20mil Rogers PCB with $128 \times \Phi 0.25mm$ via hole beneath the package backside and the reference temperature T_{case} ($85^{\circ}C$) apply on the groundside of the PCB, the total thermal resistance $R_{\theta JC}$ (TBD)°C/W.
- (4) The power dissipation in the table is overall dissipation which include Carrier PA, Peaking PA and driver PA.

Table 3. ESD Protection Characteristics

Test Methodology	Class Voltage
Human Body Model(HBM) (JEDEC Standard JESD-A114)	TBD
Charged Device Model (CDM) (JEDEC Standard JESD22-C101F)	$\pm 1000V$

Table 4. Electrical Characteristics

Parameter	Condition	Min	Typ	Max	Unit
Frequency Range		4.8		5.0	GHz
Carrier Quiescent Current (I_{DQ})			55		mA
Peak PA Gate Quiescent Voltage (V_{PEAK})			-4.9		V
Power Gain @ P1dB	Freq=5.0GHz	28	29		dB
P1dB	Freq=5.0GHz		47		dBm



P3dB	Freq=5.0GHz		47.5		dBm
Drain Efficiency@ P3dB	Freq=5.0GHz		55		%

Unless otherwise noted: TA = 25°C, V_D =48 V, Pulse Width=20 us, Duty cycle=10%

Load Mismatch of per Section (On Test Fixture, 50 ohm system): f = 5.0 GHz

VSWR 10:1 at P3dB pulse CW Output Power	No Device Degradation
---	-----------------------

Reference Circuit of Test Fixture Assembly Diagram




Figure 1. Test Circuit Component Layout

Table 5. Test Circuit Component Designations and Values

Component	Value	Description
U1	SMAV4850-55	PA Module
C1、C6、C7、C9	3.9pF	ATC600S
C2、C8、C10	10uF	GRM32EC72A106ME05
C3、C4、C5	1000pF	GGD188R72A102KA02

TYPICAL CHARACTERISTICS




Figure 2. Power Gain and Drain Efficiency as Function of Pulsed CW Output Power




Figure 3. WCDMA performance at Pout=39.5dBm





Figure 4. Network analyzer output, S11/S21



Package Dimensions


10*6 Plastic Package



Notes:

1. All dimensions are in mm;
2. The tolerances unless specified are ± 0.2 mm.

Mounting Footprint Pattern



Notes:

1. All dimensions are in mm;
2. Vias are required under the backside paddle of this device for proper RF/DC grounding and thermal dissipation. ALL vias are PTH to ground.



Revision history

Table 6. Document revision history

Date	Revision	Datasheet Status
2020/5/29	Rev 1.0	Preliminary Datasheet
2020/8/13	Rev 1.1	Define Pin 16 as BE
2021/3/2	Rev 1.2	Modify fixture picture
2021/5/2	Rev1.3	Add Rth information, modify Vgs-peak, modify fixture picture

Application data based on HJ-20-12

Disclaimers

Specifications are subject to change without notice. Innogrations believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Innogrations for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Innogrations. Innogrations makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Innogrations in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Innogrations products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Innogrations product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility. For any concerns or questions related to terms or conditions, pls check with Innogrations and authorized distributors

Copyright © by Innogrations (Suzhou) Co.,Ltd.