



2.7-3.5GHz, 28V 200W, GaN Fully matched PA Module


Description

The GMAH2735-200H2 is a 200-watt, single stage integrated Power Amplifier Module, designed for broad band applications, with frequencies from 2.7 to 3.5GHz.

The module is 50 Ω input/output matched and requires minimal external components.

The module implements multiple GaN active dice and its matching network within highly compact 24*17mm metal RF package with excellent capability for heat dissipation.

It is recommended to use it only for pulsed application



$V_{DS}=28V, I_{DQ}=350mA(V_{GS}=-2.7V), 20\mu s, 10\%$

Freq (MHz)	P1dB Gain(dB)	Psat (dBm)	Psat (W)	Psat Eff(%)
2700	13.04	53.92	246.4	66.2
2800	15.28	53.46	221.9	63.6
2900	16.05	53.43	220.5	60.3
3000	15.91	53.74	236.5	59.0
3100	15.57	53.75	237.2	56.5
3200	15.94	53.82	241.2	55.1
3300	15.76	53.9	245.6	55.1
3400	15.52	53.8	239.6	56.3
3500	13.91	53.42	220.0	58.4

Product Features

- Operating Frequency Range: 2.7-3.5GHz
- Operating Drain Voltage(Recommended): +28V (32V with increased power capability)
- 50 Ω Input/Output (External DC block capacitor needed)
- $Psat \geq 200W$ (Pulse)
- Small signal gain: >14dB, Power gain: >11dB @200W
- Minimum Psat efficiency: >55%
- 24*17 mm metal RF package
- Compliant to Restriction of Hazardous Substances (RoHS) Directive 2002/95/EC

Applications

- S band pulsed amplifier



Table 1. Maximum Ratings

Rating	Symbol	Value	Unit
Drain--Source Voltage	V_{DSS}	150	Vdc
Gate--Source Voltage	V_{GS}	-10 to +2	Vdc
Operating Voltage	V_{DD}	+36	Vdc
Storage Temperature Range	T_{stg}	-65 to +150	°C
Case Operating Temperature	T_c	+150	°C
Operating Junction Temperature	T_j	+225	°C

Table 2. Thermal Characteristics

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction to Case $T_c = 25^\circ\text{C}$, $P_{out} = 300\text{W}$, FEA	$R_{\theta JC}$	TBD	$^\circ\text{C/W}$

Typical application circuit



Reference	Footprint	Value	Quantity
C1, C2, C3, C4	0805	12pF/250V	4
C5, C6	1210	10uF/100V	2
C7		470 uF/63V	1
R1	0603	10R	1
U1	H2	GMAH2735-200H2 ^{V2.1}	1



TYPICAL CHARACTERISTICS

Figure 1. Network analyzer output S11/S21 (Pin=0dBm), Vds=28V, Idq=600mA





Figure 2. Power Gain, Efficiency as function of Pout at 28V









Figure 3. Pout and Efficiency ,Power gain at fixed input 41dBm



Pout vs Frequency




Efficiency vs Frequency



Efficiency vs Power Gain

Package Dimensions (Unit:mm)



Revision history

Table 6. Document revision history

Date	Revision	Datasheet Status
2026/6/1	Rev 1.0	Preliminary datasheet

Application data based on ZBB-26-09

Disclaimers

Specifications are subject to change without notice. Innigration believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Innigration for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Innigration. Innigration makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Innigration in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Innigration products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Innigration product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility. For any concerns or questions related to terms or conditions, pls check with Innigration and authorized distributors
Copyright © by Innigration (Suzhou) Co.,Ltd.